

CLD FenceSafe Securus SR1



Temporary Fencing System Rated to LPS 1175 (SR1) Issue 7

Minimum delay of 60 Seconds against attack

Offering safety, security and sustainability, CLD's FenceSafe Securus S1 system is the world's first LPS1175 security rated temporary fencing system.

Using our innovative foundation free cantilevered FenceSafe base coupled with our Securus 358 mesh fencing, the system is guaranteed to offer at least 60 seconds delay against attack.

Both the base and the Securus panels can be reused. The panels can even be used in a permanent fenceline.

Ideal for

- Major Events
- Utilities
- Crowded places
- Airports

Conforms to



Isometric View



Exploded view of post and fixing details for the FenceSafe Securus SR1 System
This product has additional features not demonstrated for security reasons



Key Features

Overlapping panels for added security

Full length clamp bar with no external fixings

Anti-Climb 358 mesh panels

Through bolt with rear fastening

Scan the QR code to find out more



CLD FenceSafe Securus SR1






Temporary Fencing System Rated to LPS 1175 (SR1) Issue 7

Product Technical Information

Standards:	LPS 1175 (SR1) Issue 7 BS1722-14: 2017 BS EN ISO 1461:2009 BS EN 13438:2013 Secured by Design - Police Preferred Specification
Panel Width:	2518mm
Wire Diameter:	4mm nominal
Mesh Size:	76.2 × 12.5mm mesh
Height:	2440mm
Nominal height:	2.4m (other heights available uncertified)
Finish:	Polyester powder-coated to minimum 80 microns. Any RAL colour
Top Edge Projection:	Nil
Panel Installation	Nil
Topping Options:	Barbed and razor wire, cranked and straight available if required
Posts:	60×60 RHS post, galvanised after manufacture and polyester powder-coated to match fencing
Post dimensions:	60 × 60mm. Floating corner posts 60 × 60mm
Post centres:	1220mm +/- 9mm
Fixings:	41mm x 21mm clamping channel and CLD SafeTFix hidden fixing system
Foundations:	CLD FenceSafe base unit, with 4-way adjustable bracket and 200kg of ballast. System to be designed in accordance with BS6399-2 or BS EN 1991 for area of use.
Warranty	Minimum of 15 years against manufacturing defects.

System Details



Disclaimer

Fencing should be installed in accordance with BS 1722-14. Every care has been taken to ensure that all information provided on this data sheet is accurate. CLD Fencing Systems Ltd reserves the right to change product specification at any time. Please ensure that you have the latest information which can be found on our website or by contacting our team.

Document Reference - 20221031_CLD_FenceSafe_Securus_SR1_DS

CALL 01270 764751 VISIT WWW.CLD-SYSTEMS.COM