

CLD Dulok 25 S1

Double wire panel system to LPS 1175 A1 (SR1) Issue 8



Minimum Delay of 60 seconds delay against attack

Dulok is a highly versatile mesh fencing system, which offers an aesthetic and cost-effective solution where visibility is required. This security-rated version of Dulok features twin 8mm horizontal wires either side of the 6mm vertical wire (traditionally known as 868), and no visible fixings, slowing down potential intruders.

For full technical information please see overleaf.

Ideal for

- Schools
- Sports and Leisure
- Multi-use games areas
- Public spaces

Conforms to



Isometric View



Exploded view of post and fixing details for the CLD Dulok 25 S1

Key Features

High security anti-cut double wire panels

Secured by Design accredited system

Full range of RAL colours available

Smaller aperture of 25mm making it more difficult to climb or cut

Scan the QR code to find out more



CLD Dulok 25 S1

Double wire panel system to LPS 1175 A1 (SR1) Issue 8



Product Technical Information

Standards: LPS 1175 A1 (SR1) Issue 8 BS1722-14: 2017
BS EN ISO 1461:2009 BS EN 13438:2013
Secured by Design - Police Preferred Specification

Panel type: Mesh and wire. Single vertical and double horizontal wires. Galvanised and powder-coated to minimum 60 microns

Panel width: 2508 mm

Height: 1830mm to 5070mm. Heights of 3030mm and above are made up of 2 or more panel

Nominal heights: 1.8m to 5m

Finish: Polyester powder-coated to minimum 60 microns.
Any RAL colour including marine grade and metallics.

Top Edge projection: 30mm

Panel installation: Bottom of panel minimum 50mm above ground

Topping options: Options available on request

Posts: RHS, galvanised after manufacture and polyester powder-coated to match fencing

Post dimensions: 80mm x 40mm to 120mm x 60mm depending on height of panel


Post centres: 2516mm

Fixings: 40mm x 5mm full length clamp bar. M8 x 40mm Sheardrive™


Foundations: Set posts in holes minimum 300mm square or 400mm diameter x 800mm deep.
Note: Contractor/ client is responsible for the foundation size suitable for the ground conditions and height of fence

Warranty Minimum of 15 years against manufacturing defects.


System Details




Plan of end post



Plan of panels in line



Plan of internal corner



Plan of external corner

Disclaimer

Fencing should be installed in accordance with BS 1722-14. Every care has been taken to ensure that all information provided on this data sheet is accurate. CLD Fencing Systems Ltd reserves the right to change product specification at any time. Exact dimensions should be confirmed prior to installation.

Document Reference - 20221111_CLD_Dulok_25_S1_DS

CALL 01270 764751 VISIT WWW.CLD-SYSTEMS.COM