

# CLD SlideMaster

Cantilever Sliding Gates



CLD's SlideMaster gates have been specially developed to blend in seamlessly with a CLD fence line. Available in different mesh options to match the fence, set in a heavy duty aluminium frame, SlideMaster gates are available up to 10 metres wide each.

The track is totally enclosed, preventing damage from vandals.

## Ideal for

- Industrial and Retail Parks
- Car Parks



## Conforms to



## Isometric View



## Key Features

Available in different mesh options to match fence line

Double or single leaf opening

Enclosed track

Scan the QR code to find out more



# CLD SlideMaster

Cantilever Sliding Gates



## Product Technical Information

<b>Standards:</b>	BS1722-14: 2017
<b>Description:</b>	Open mesh aluminium security gate system with steel mesh infill
<b>Configuration:</b>	Single leaf sliding to left or right or double leaf
<b>Infill Panels:</b>	Options to be chosen from the CLD range of mesh fencing panels to match fenceline. See mesh type Q40 for more information.
<b>Heights:</b>	Various heights available to suit customer requirements. Please contact CLD for more information.
<b>Nominal heights:</b>	n/a
<b>Widths (Select as required):</b>	Single leaf opening size from 1000mm to 10000mm Double leaf opening size from 2000mm to 20000mm
<b>Gate Construction:</b>	Gate consists of main aluminium upright tower to house motor and all safety equipment. Main gate frame supported on custom made cantilever beam. Frame constructed from 75×75mm Aluminium box with mesh infill as above. 230v single phase power required to power the 100% duty cycle motor with a gate opening speed of 4 seconds per metre.
<b>Fixing:</b>	Main control tower, park post and support rollers to be rawl-bolted to cast concrete footings all as per manufacturer's drawings. Setting out not to commence until site specific drawings have been issued by manufacturer.
<b>Locking:</b>	Auto
<b>Finish:</b>	Polyester powder-coated to match mesh infill panels. Any RAL colour
<b>Foundations:</b>	Concrete slab foundation to suit gate size. Please contact CLD Physical Security Systems.
<b>Other requirements:</b>	Please allow for 60mm safety cell ducting between gate tower and park post, and main power feed to tower, as per drawing
<b>Warranty:</b>	Minimum of 15 years against manufacturing defects.

## Disclaimer

Fencing should be installed in accordance with BS 1722-14. Every care has been taken to ensure that all information provided on this data sheet is accurate. CLD Fencing Systems Ltd reserves the right to change product specification at any time. Please ensure that you have the latest information which can be found on our website or by contacting our team.

Document Reference - 20230106\_CLD\_SlideMaster\_DS

**CALL 01270 764751 VISIT [WWW.CLD-SYSTEMS.COM](http://WWW.CLD-SYSTEMS.COM)**